

ENVIRO D-GREASE TECHNICAL DATA SHEET

PHYSICAL PROPERTIES

Product Name	Enviro D-Grease
Physical Form	Liquid
Color	Clear Blue
Odor	Lemon
Solubility	100%
pH	10.0
Boiling Point	212°F
Specific Gravity (water = 1)	1.05

Complete information on health hazards, protective equipment, handling precautions, environmental hazards and disposal is listed in the current Enviro D-Grease Safety Data Sheet (SDS) for this product.

PRODUCT SUMMARY

Enviro D-Grease is a heavy-duty, water-based, biodegradable alkaline degreaser. This concentrate formula must be diluted prior to use and is commonly applied to clean caked on grease, parts and the exterior surface of tanks.

Enviro D-Grease is commercially available in 5-gallon buckets and 55-gallon drums from Oklahoma City, Oklahoma and Houston, Texas.

PRODUCT BENEFITS

- Versatile
- High performance with low usage costs
- Quick, easy, and simple to use

FIELD MIXING PROCEDURES

Mixing Concentrates

Enviro D-Grease is usually delivered as a concentrate and **must** be diluted with water to work properly. Solutions can be formulated by premixing or eduction. It is not necessary to provide high shear agitation when preparing a

batch of solution since Enviro D-Grease is 100% soluble in water. It is recommended that when preparing the solution you first add the water into the mix container and then follow by the addition of Enviro D-Grease.

For premixing, the following procedure may be used:

1. Add the correct amount of water to the container.
2. Depending on the desired strength, add the correct amount of Enviro D-Grease to the container.

Suitability of Purpose

This material is made available for the use by professionals or persons having technical skills to be used at their own discretion and risk. Nothing herein is to be taken as a license to use Enviro D-Grease without the proper permits, approvals, etc. of the appropriate regulatory agencies, nor are the protocols provided as instructions for any site specific application of Enviro D-Grease. All Enviro Clean products should be used in compliance with all federal, state, and local rules and regulations.

APPLICATION PROTOCOLS

For specific protocols and application rates, please refer to the product label or consult with the manufacturer or authorized distributor for additional guidance.

Equipment Cleaning & Parts Washing

Light Soil: Dilute 16 oz. of product to 1 gallon hot or cold water and spray or mop on surface. Allow contact time of 3 to 5 minutes and scrub gently. Rinse with clean water.

Tough Soil: Dilute 32 oz. of product to 1 gallon hot or cold water. Apply to area as above or may also be applied with brush or through power washer. Rinse thoroughly and dispose of as local rules may apply. Do not allow product to dry on surface prior to rinsing. Test surface prior to application.